



WOW


WATER-ON-WATER™ REVERSE OSMOSIS

WOW50-20-209-001

- Faster Easier Installation
- Compact size fits in half the space of other units
- Patented **water-on-water™** tank provides constant flow to the last drop
- Environment-friendly – uses up to 500% less waste water
- No air charge needed
- Patented manifold design increases reliability
- Patented CPU valve with only one moving part = higher reliability
- Operates as low as 20 psi
- Safe and convenient, **sanitary rapid-change** filters offer consumer friendly maintenance

Specifications	
Model:	WOW50-20-209-001
Temperature Range:	40° F (4.44° C) - 100° F (37.77° C)
Pressure Range:	20 - 125 psi (1.38 - 8.62 Bar)
System Production Rate:	30.5 gpd (113.56 Lpd)
Efficiency Rating:	27.50%
TDS Rejection:	95.40%
Dimensions:	14" x 9-1/2" x 10-1/2"
Weight:	10 Lbs

The installation of this RO System needs to comply with all Local and State Laws and Regulations



This WOW-50 RO System is Certified by IAPMO R&T against NSF/ANSI 58 for the reduction of Claims specified in the Performance Data Sheet

Efficiency rating means the percentage of the influent water to the system that is available to the user as reverse osmosis treated water under operating conditions that approximate typical daily usage

The Many Uses of WOW Water

- | | |
|----------------|----------------------|
| Cooking | Rinsing Hair |
| Juices & Mixes | Plants |
| Coffee & Tea | Steam Irons |
| Ice Cubes | Windshield |
| Humidifiers | Wiper Fluid |
| Aquariums | Automobile Batteries |

Do not use with water that is micro-biologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

Compact Size. Easier Install. More Reliable.



WOWwater.com

WOW Water Systems Performance Data Sheet V1.3.15.19

* Results may vary depending on water conditions

Topper Manufacturing Co. - A Beall Development - 23880 Madison Street, Torrance, CA 90505 - U.S. and foreign patents issued and pending.

SHIPPING SPECIFICATIONS

PART NUMBER	MODEL	DESCRIPTION	CARTON QTY	CARTON DIMENSIONS	CARTON WEIGHT
WOW50-20-209-001	WOW50	4 Stage Reverse Osmosis System Hardware not included	1	16"L X 11"W X 13"H	10 LBS
20-201-001	WOW50	Pre Filter Cartridge	20	16"L X 13"W X 11"H	13 LBS
20-202-001	WOW50	Post Filter Cartridge	20	16"L X 13"W X 11"H	18 LBS
20-250-001	WOW50	RO Membrane Cartridge	20	16"L X 13"W X 11"H	17 Lbs
PART NUMBER	MODEL	DESCRIPTION	PALLET QTY	PALLET DIMENSIONS	PALLET WEIGHT
WOW50-20-209-001	WOW50	4 Stage Reverse Osmosis System Hardware not included	50	40"L X 48"W X 68"H	540 LBS
WOW50-20-209-001	WOW50	4 Stage Reverse Osmosis System Hardware not included	25	40"L X 48"W X 42"H	290 LBS

PERFORMANCE

MODEL WOW50-20-209-001

This WOW50 RO system is certified by IAPMO R&T against NSF/ANSI 58 for the reduction of claims specified in this document.

System Production Rate: 30.5 gpd (113.56 lpd)

Efficiency Rate: 27.5%

TDS Rejection: 95.4%



This WOW-50 RO System is Certified by IAPMO R&T against NSF/ANSI 58 for the reduction of Claims specified in the Performance Data Sheet



23880 Madison St., Torrance, CA 90505

310-375-5000 ~ 866-790-8911

wowwater.com

Efficiency rating means the percentage of the influent water to the system that is available to the user as reverse osmosis treated water under operating conditions that approximate typical daily usage

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts